


Ziligen© Data Sheet

Name	Z 15/3 F/V1-38 ANT LIGHT GREEN		
Stock Number		Update Date	Feb 5, 2021, 7:57:05 AM

Material Structure			
Total Thickness	3.80	+/- 0.10	
Number of Plies	3		
Tension Member Material	PES		
Tension Member Structure	Rigid		
Weight	4.90		
Working Temperature	-10 °C	70 °C	

Top Cover		Profiles Application	
Material	Pvc	Top Cover	Yes
Color	Light Green	Bottom Cover	Yes
Thickness	1.00 mm	Sidewalls	No
Pattern	GL		
Hardness	74 sHa		
Electrostatic Properties	Nonantistatic		
Internal Cover		Special Characteristic	
Material	Pvc	FDA Food	Yes
		EU Food Regulation	Yes
		Animal Oil Resistance	No
		Vegetal Oil Resistance	No
		Minerals Oil Resistance	No
		Limited Resistance to Animal Oil and Greases	No
		Excellent Abrasion Resistance	No
		Cut Resistant	No
		Low Friction	No
		Silent Fabric	No
		ATEX	No
Bottom Cover			
Material	PES		
Color	Natural		
Thickness	0.00 mm		
Pattern	-		
Hardness	0 sHa		
Electrostatic Properties	Antistatic		

Tension Member		Support Surface	
Breaking Load	180 N/mm	Slider Bed	Yes
Working Load %1 Elongation	15 N/mm	Rollers	No
		Troughed Application	No
Drum Diameter	100 mm		
Splicing		Friction Coeff. Bottom Cover	
Overlap Splice	Yes	On Steel	0.00 / 0.00
Z Splice	Yes	On Wood	0.00 / 0.00
Mechanical Fasteners	RS - 62	On Plastic	0.00 / 0.00
Longitudinal Splice	Yes		
Food App(TS-EN1186-1/15)	Yes	Maximum Production Width	3000 mm
		Flame Reterdant	No

Z-Splice Press Setup		Overlap Splice Press Setup	
Upper Plate Temperature	155 °C	Upper Plate Temperature	155 °C
Lower Plate Temperature	155 °C	Lower Plate Temperature	155 °C
Stand By Time in Press	0 min	Stand By Time in Press	0 min
Press Pressure	3 bar	Press Pressure	3 bar
Glue	PVC Foil	Glue	Pu + Hu

General Information	
Product Group	Pvc Conveyor Belt
Market Segment	

Create Date: Oct 29, 2021, 10:56:30 AM GMT

Create PDF